Test report : CEE-0392/25-1
CEE-0346/25-1

NB : 1722

CE 25

Type: B
Fuel: Wood Logs

SOLZAIMA

Small Box Glass Door; Nº Série 01-06-00---

Solzaima, SA., Rua da Cova da Areia (E.M. 605), 695, 3750-071 Aguada de Cima
Águeda- Portugal - Made in Portugal

Nº DOP DD-099-B

Emissions (13%O_2):	Nom	Part
CO :	1250 mg/m^3	-
NOx :	200 mg/m^3	-
OGC :	100 mg/m^3	-
PM :	40 mg/m^3	-

Performance:	Nom	Part
P :	9,4 kW	-
P_W :	-	-
P_{SH}:	9,4 kW	-
η :	80 %	-
p :	12 Pa	-

EN 16510-1:2022 / EN 16510-2-1:2022

Flue gas outlet temperature (Nom-Part):	285 ºC- -
Diameter of the flue gas outlet :	150 mm
Fire safety of installation to the chimney :	T 400 G
Seasonal space heating efficiency (η_s) :	72 %
Energy Efficiency Index (EEI) :	106
Energy Efficiency Class :	A
The permissible maximum water operation pressure (P_W - bar):	-
Protective Insulation acording to manufacture r's instructions :	-
Power supply voltage (E) :	-
Power supply frequency (f) :	-
Maximum electric power input (W_{max}) :	-
Mass of the appliance (m) :	137 kg
Fuel Type :	Type I
Operation Type :	INT - Intermittent

Minimum distances to combustible materials

Bottom d_B = 0 mm
Ceiling d_C = 1500 mm
Front d_P = 1500 mm
Non-Comb d_{non}= -

Floor d_F = 1500 mm
Rear d_R = 400 mm
Side d_S = 400 mm

Side radiation area d_L = 1500 mm



Only use recommended fuels / Read and follow the manual / Shared flow prohibited